



# ZHTM

*Heat-shrinkable, flexible tubing with low toxicity for fire safety applications*



## Applications

A flexible, thick-wall, heat-shrinkable tubing to be used in conjunction with -100 molded parts and Zerohal cable to form Raychem System 100, this material exhibits excellent fire safety characteristics combined with low smoke emission and low evolution of acid gases while retaining good mechanical and fluid-resistance properties. Used for insulation and protection of cables, harnesses, and electrical and electronic components in enclosed spaces, such as in marine applications, mass transit systems, and offshore installations, to reduce toxicity risks, or where equipment would be irreparably damaged by corrosive products of combustion.

## Features and benefits

- 2:1 shrink ratio.
- Low smoke emission.
- System 100 tubing.

## Installation

Minimum shrink temperature: 80°C  
 Minimum full recovery temperature: 121°C

## Operating temperature range

-30°C to 105°C

<i>Available in:</i>	Americas	Europe	Asia Pacific
	■	■	■

<i>Specifications/approvals</i>				
Series	Military	Agency	Industry	Raychem
ZHTM	Def. Stan. 59-97 Issue 3 Type 8	BS 4G-198 Part 3 Type 15 VG 95343 Part 5 Type L VDE 0341/Pt 9005	BR 1326A	RW-2058

**Fax-on-demand**

US only (800) 260-9099

Outside US (650) 257-2301

Visit our website at [www.tycoelectronics.com](http://www.tycoelectronics.com)**Product dimensions (mm/in)**

Size	Inside diameter		Recovered wall thickness*
	Minimum expanded as supplied	Maximum recovered after heating	After heating
3/1.5	3.0 (0.118)	1.5 (0.059)	0.70 ± 0.10 (0.028 ± 0.004)
5/2.5	5.0 (0.197)	2.5 (0.098)	0.75 ± 0.12 (0.030 ± 0.005)
8/4	8.0 (0.315)	4.0 (0.157)	0.80 ± 0.15 (0.031 ± 0.006)
12/6	12.0 (0.472)	6.0 (0.236)	0.90 ± 0.15 (0.035 ± 0.006)
18/9	18.0 (0.709)	9.0 (0.354)	1.00 ± 0.18 (0.039 ± 0.007)
24/12	24.0 (0.945)	12.0 (0.472)	1.10 ± 0.20 (0.043 ± 0.008)
40/20	40.0 (1.575)	20.0 (0.789)	1.30 ± 0.23 (0.051 ± 0.009)
50/30	50.0 (1.969)	30.0 (1.181)	1.50 ± 0.28 (0.059 ± 0.011)

\*Wall thickness will be less if tubing recovery is restricted during shrinkage.

**Ordering information**

Color	Standard	Black (-0)
Size selection	Always order the largest size that will shrink snugly over the component to be covered. Special order sizes are available upon request.	
Standard packaging	On spools.	
Ordering description**	Specify product name, size and color (for example, ZHTM 8/4-0).	

\*\*Europe only. For supply to Def Stan and BS add -DS or -BS to ordering description.